



**CUSHMAN®**

# HAULER® 800X



## MAKE TOUGH JOBS A WALK IN THE PARK.

Every part of the Cushman® Hauler® 800X utility vehicle is designed to take on tough jobs. From an 8.4-cubic-foot cargo bed, to bench seating, to a lifted suspension and trail tires, it can navigate off the beaten path without breaking a sweat. With the option of a fuel-efficient 13.5 hp Kawasaki® gas-powered engine, or a quiet, zero-emissions 48V AC electric drivetrain, the power to boost performance is in your hands. It's time to see what utility really means. Take the Hauler 800X for a drive.

**LET'S WORK.®**

**13.5 HP**  
KAWASAKI®  
GAS ENGINE

**8.4 CU FT**  
CARGO BED

**16.5 MPH**  
MAX SPEED

**48V AC**  
ELECTRIC  
DRIVETRAIN



# CUSHMAN® HAULER® 800X



LIFTED SUSPENSION  
W/ HIGH GROUND CLEARANCE



BED DIVIDERS

USB & 12V OUTLET

## OPTIONS & ACCESSORIES

- Improved Surface Tires\*
- Brake Lights\*
- Taillights\*
- Fuel/Oil Gauge (gas vehicle only)\*
- On-board Charger (electric vehicle only)\*
- Premium Steering Wheel\*
- 2" Rear Receiver Hitch\*
- LED Headlights with High/Low Beam
- ROPS-Certified Cab
- Bed Dividers
- Long-Handled Tool Holder
- Cargo Mesh Netting
- Weather Enclosure
- USB Outlet
- 12-Volt Outlet
- Canopy Storage Net
- Rearview Mirror

\*Included in Commercial Package



COVERED WITH THE 2-YEAR CUSHMAN  
CARE TOTAL PROTECTION WARRANTY

	ELECTRIC MODEL	GAS MODEL
<b>BODY &amp; CHASSIS</b>		
FRAME	Welded Steel w/ E-Shield e-coat plus DuraShield™ Powder Coat	
BODY & FINISH	Injection Molded TPO (Front) / Injection Molded PP (Rear)	
STANDARD COLOR	Patriot Blue	
<b>DIMENSIONS</b>		
OVERALL LENGTH	110 in (279.4 cm)	
OVERALL WIDTH	49 in (125 cm)	
OVERALL HEIGHT	51 in (129.5 cm) ( w/o Roof) / 74 in (188 cm) (w/ Canopy)	
WHEEL BASE	65.5 in (166.4 cm)	
WHEEL TRACK	37 in (94.0 cm) Front / 38 in (96.5 cm) Rear	
GROUND CLEARANCE	5.5 in (14.0 cm)	
CARGO DECK CAPACITY	8.4 cu ft (0.24 m³)	
CARGO DECK DIMENSIONS	44.5 in x 28.5 in x 12 in (113 cm x 72 cm x 30.5 cm)	
CARGO DECK MATERIAL	Roto-Molded Polyethylene	
<b>POWER</b>		
POWERTRAIN	48V AC	4-Cycle, 24.5 ci (401cc) Cylinder
VALVE TRAIN	N/A	Single Cylinder OHV
HORSEPOWER (KW)	4.4 hp (3.3 kW) Continuous	13.5 hp (10.1 kW) Exceeds SAE J1940 Std.
ELECTRICAL SYSTEM	48V	Starter/Generator. Solid State Reg.
BATTERY (QTY/TYPE)	Six, 8V Deep Cycle	One, 12V Maintenance Free
BATTERY CHARGER	48V DC PowerWise QE, 120V AC, UL/CSA	N/A
KEY OR PEDAL START	Pedal	
AIR CLEANER	N/A	Replaceable Dry Cartridge
LUBRICATION	N/A	Pressurized Oil System
OIL FILTER	N/A	Spin-On
COOLING SYSTEM	N/A	Air Cooled
FUEL CAPACITY	N/A	5.6 Gallon (21.2 L) Tank
SPEED CONTROLLER	235 Amp AC Controller	N/A
DRIVE TRAIN	Motor Shaft Direct Drive	Continuously Variable Transmission
TRANSAXLE	Differential w/ Helical Gears	
GEAR SELECTION	Dash-Mounted Forward-Neutral-Reverse	Forward - Reverse
REAR AXLE RATIO	16.99: 1	11.47: 1 (Forward) 14.53: 1 (Reverse)
<b>PERFORMANCE</b>		
SEATING CAPACITY	2-Person (Bench)	
WEIGHT W/O BATTERIES	756 lb (342.9 kg)	800 lb (362.9 kg)
CURB WEIGHT	1122 lb (508.9 kg)	850 lb (385.6 kg)
VEHICLE LOAD CAPACITY	725 lb (328.9 kg)	
BED LOAD CAPACITY	325 lb (147.4 kg)	
TOWING CAPACITY	500 lb (226.8 kg)	
OUTSIDE CLEARANCE CIRCLE	18.9 ft (5.8 m)	
SPEED	16.5 mph ± 0.5 mph (26.5 kph ± 0.8 kph)	
<b>STEERING &amp; SUSPENSION</b>		
STEERING	Self-Compensating Rack & Pinion	
SUSPENSION	Leaf Springs w/ Hydraulic Shock Absorbers	
SERVICE BRAKE	Rear Wheel Mechanical, Self-Adjusting Drum	
PARKING BRAKE	Self-Compensating, Single-Point Engagement	
TIRES (FRONT & REAR)	K500 20 x 8-10 (6 Ply Rated)	

[www.cushman.com](http://www.cushman.com)

©2018 Textron Specialized Vehicles Inc. All rights reserved. Features and specifications of the vehicles are subject to change without notice. Vehicle as photographed may include options not included on base model.

82291-G5 (Rev. 11/2017)